



PLENAFILL®

"27U Scalable blanking panel that is quick to install"

Good practice in the Data Centre requires that unused U space is sealed to prevent hot exhaust air from finding its way to the air intake area at the front of the cabinet. PLENAFILL® Blanking panels are supplied in 27U sheets and can be cut to any required size, avoiding the need to store several sizes of traditional blanking panel. PLENAFILL® is a proven solution to eliminate Hot Spots and reduce overall cabinet temperatures.

Features

- Pack of 10 PLENAFILL® Blanking panels equals 270 1.75" (44mm) rack mount U's.
- Fits all 19" EIA server racks.
- Fire rated material: ULVO class 94.
- Quickly and easily fill large sections of un-occupied rack space, stopping by-pass air flow, and recirculation of hot exhaust air.
- No more guessing at how many blanking panels are needed.
- Fits snugly against EIA rails with no air gaps between U's.
- Scalable / Less Storage Space / Less Freight Cost.
- Cuts easily for less than 1U spaces.
- Installs in seconds with snap rivets or thumb screws - no tools, cage nuts or grommets required!



49-PF-PT - PlenaTool



Blanks Less Than 1U!



49-PF-BR - Square Hole Rivets

Specifications

Part Number: 49-PF-27U-10* - Dark Grey

49-PF27U-10W* - White

Dimension: 47.25" x 19.25" x .040"

1200mm x 489mm x 1mm

Weight: Approx. 1.40lbs (0.63Kg) each

Total shipping weight per pack of 10 = 17.5lbs (8Kgs)

* Fasteners not included, should be ordered separately



PLENAFILL®

is Now Available in White

Features

- Same characteristics as standard PLENAFILL®.
- Improvement in light levels, due to reflectiveness of white material.
- Instantly identify areas of unused rack space.
- Looks better in light coloured racks, compared to standard PLENAFILL®.